



Performance Chemicals

FIRE RETARDANTS

Koppers FirePRO and PROTIM Frameguard



Photograph courtesy of Wilkinson Eyre Architects & PTG Treatments

www.kopperspc.eu

Koppers FirePRO



Fire Retardant for Internal Timber

Fire Retardant Treated Wood Products

Koppers FirePRO is an interior high temperature fire retardant chemical formulation based on proprietary Koppers technology.

Independent testing performed in accordance with industry standards has shown Koppers FirePRO products exhibit fire retardant performance properties without significantly compromising other critical engineering properties such as strength, durability, corrosivity, and hygroscopicity.

Koppers FirePRO is a WPA Approved Product under their Flame Retardant Quality Scheme.

PROTIM Frameguard®



Flame Retardant and Preservative for Timber Frames

What is Protim Frameguard®?

Protim Frameguard® is a flame retardant and preservative low pressure treatment system developed to reduce flame spread in framing timbers and plywoods during construction and to impart preservative protection against fungal decay and insect attack to Use Class 2, 60 years desired service life, in accordance with BS 8417:2011 Preservation of Wood - Code of Practice.

Protim Frameguard® has been tested by Building Research Establishment (BRE) in accordance with BS 476 Part 7, the UKTFA 'FR Build' Scheme and complies with the NHBC preservation requirements for framing timbers embodied in Chapters 2.3 and 6.2 of the 2006 edition of NHBC Standards.

Application

Koppers FirePRO products are permitted for use in above ground interior applications where the adopted building regulations permit the use of wood products or fire retardant treated wood products (FRTW) such as roof systems, sheathing, joists and such like. It can also be used in other interior applications such as exhibition stands. The specifier and/or end user is responsible for reviewing the test data on Koppers FirePRO FRTW products to determine if they are acceptable for the intended end use.

Koppers FirePRO FRTW may be used in above ground external situations where it is effectively protected from direct rainfall and weathering. External grade wood coatings may give adequate long term protection, in combination with a programme of planned maintenance. Check with a coating manufacturer before use.

Standards and Specification Information

Koppers FirePRO fire retardant treated wood products (FRTW) have been tested to BS EN 13501-1 Fire classification of construction products and building elements. These tests are commonly referred to as 'reaction to fire tests'. Reaction to fire tests are commonly called up in regulations in both the building and transport sectors. The classifications of flammability are A1, A2, B, C, D, E and F.

Koppers currently holds approvals for many of the most commonly specified species. Below is a list of just some of the approvals held.

- Softwood Plywoods (Spruce, Pine...)
- Hardwood Plywoods (Far Eastern, Birch...)
- Softwoods (Spruce, Western Red Cedar...)
- Hardwoods (Oak, Poplar...)
- Thermally Modified Wood (Thermowood...)



Further materials are undergoing testing on a continuous basis, please contact us for a comprehensive list. Please check with Koppers for specific sizes tested and approval classification achieved. Koppers FirePRO treated wood products can also be CE marked.



Koppers FirePRO is able to meet the requirements of HR (humidity resistant) treatment and DI (dry internal) specifications. Koppers FirePRO is approved by London Underground as a suitable fire retardant treatment for timbers to be used in their construction and maintenance projects, approval reference ID 1327.

Why Protim Frameguard®?

There is an ongoing desire to enhance confidence in timber frame as a secure and safe construction system. Fire risk management during the construction phase requires a matrix management approach. Flame retardant treatment protection of timber framing can provide an important, additional element to this management matrix. Flame retardant treatment can help reduce the rate of flame spread on the treated timber. This allows more time for other risk management measures to be effective and so minimize the consequences of a fire. Flame retardant treatment does not stop wood from burning altogether and must not be relied upon as the sole means of managing fire risk on timber frame construction sites.

Why is Protim Frameguard® different?

Flame retardant treated wood products have been sold in the UK for years and the market is well established. The traditional flame retardant market is based on the use of high pressure impregnation processes, followed by kiln drying prior to use.

Protim Frameguard is a new integrated process that offers an economical approach, providing the benefit of flame retardant protection for wood products during construction and long lasting preservative protection.

How is Protim Frameguard® applied?

The Protim Frameguard treatment system can be applied in existing low pressure treatment plants with minimal engineering modification. Treatment solution is supplied by bulk tanker in ready to use form. Application is by cycles and processes broadly similar to those already in use. Solution uptakes per m3 timber will be of a similar order of magnitude as before, with no significant lasting impact on timber moisture content.


Treatment solution can be supplied with a colour tint included. Such temporary dyes are intended to give short term colour only, so as to assist in identifying material as treated in stock and on a construction site.



Treatment Process




1
The timber is transferred into the treatment vessel.




2
A vacuum pulls the air out of the vessel.




3
The preservative fills the vessel.




4
The vessel is pressurised forcing the preservative into the timber.



5
The preservative is removed and final vacuum is applied removing excess.



6
The timber has now been preserved with the preservative.



Important Information

Koppers FirePRO

- Wear a dust mask and goggles when cutting or sanding wood.
- Wear gloves when working with wood.
- All sawdust and construction debris should be cleaned up and disposed of after construction.
- Wash work clothes separately from other household clothing before re-use.
- Fire Retardant Treated Wood (FRTW) products should not be used where they may come into direct contact or indirect contact with drinking water, except for uses involving incidental contact.
- Do not use FRTW products under circumstances where they may become a component of food, animal feed, or beehives.
- Do not use FRTW products for mulch.
- Only FRTW products that are visibly clean and free of surface residue should be used.
- If wood products are wet during construction, they should be replaced.
- Do not burn treated wood. See Disposal Recommendations.
- Disposal Recommendations: FRTW products which are no longer usable (e.g. cut ends, broken boards, timber taken out of service) should not be burned. They may be disposed of in landfills, or burned in commercial or industrial incinerators or boilers, in accordance with National and local regulations.
- It should be noted that the use of some paints may affect the fire properties of the end products and care must be taken to select an appropriate paint. Always follow the coating manufacturer's instructions.
- Use fixings and other hardware which are in compliance with building regulations for the intended use.
- Use fixings, hardware or any metal products as recommended by their manufacturer.
- Mould growth can and does occur on the surface of many products, including untreated and treated wood, during prolonged surface exposure to excessive moisture conditions. To remove mould from the treated wood surface, wood should be allowed to dry. Typically, mild soap and water can be used to remove remaining surface mould.

Timber Care

Use An End Coat Preservative

Any surface exposed by drilling or cutting must be re-treated with a cut end preservative. Failure to do this will reduce the effectiveness of the preservative.

Rip sawing, thickening and planing are not permitted unless the timber is subsequently re-preserved to the original specification.

PROTIM Frameguard®

Protim is the brand name for wood pressure treated with an organic based preservative.

- Wear a dust mask and goggles when cutting or sanding wood.
- Wear gloves when working with wood.
- Wash work clothes separately from other household clothing before re-use.
- All sawdust and construction debris should be cleaned up and disposed of after construction.
- Do not burn treated wood.
- Do not use treated wood for mulch.
- Only treated wood that is visibly clean and free of surface residue should be used.
- Do not use treated wood under circumstances where the preservative may become a component of food, animal feed, or beehives.
- Treated wood should not be used where it may come into direct contact or indirect contact with drinking water.
- Use fixings, hardware or any metal products as recommended by their manufacturer.
- If wood is to be used in an interior application and becomes wet during construction, it should be allowed to dry before being covered or enclosed.
- Some preservative may migrate from the wood into soil/water or may dislodge from the treated wood surface upon contact with skin. Wash exposed skin areas thoroughly.
- Mould growth can and does occur on the surface of many products, including treated or untreated wood, during prolonged surface exposure to excessive moisture conditions. To remove mould from treated wood surfaces, wood should be allowed to dry. Typically, mild soap and water can be used to remove surface mould.
- Disposal Recommendations: Treated wood may be disposed of in landfills or burned in commercial or industrial incinerators or boilers in accordance with National and local regulations.
- Protim treated wood is compatible with most coatings, glues and sealants and can normally be coated with most wood finishes 48 hrs after treatment. Before you start, we recommend you apply the finishing product to a small test area before finishing the entire project to ensure it provides the intended result before proceeding. Protim treated wood may be glued with resorcinol, phenol/resorcinol or urea formaldehyde glues. Protim treated wood is compatible with most sealants and mastics, always follow manufacturer's recommendations.
- Use biocides safely, always read the label and product information before use.
- For more information visit www.kopperspc.eu

For more information

Visit: www.kopperspc.eu
Email: kpc@koppers.eu
Call: +44 (0)1628 486644
Fax: +44 (0)1628 476757

Protim Solignum Limited
Jubilee House
Third Avenue, Globe Park
Marlow
Buckinghamshire
SL7 1LS



FM 01724



FM 36409

* Registered Trademarks of Koppers Performance Chemicals Inc. Protim Solignum Limited is a Koppers company and trades as Koppers Performance Chemicals. Koppers is a registered Trademark of Koppers Delaware, Inc. Whilst every attempt has been made to ensure the accuracy and reliability of the information contained in this document, Protim Solignum Limited gives no undertaking to that effect and no responsibility can be accepted for reliance on this information. Information will be updated when the need arises. Please ensure you have an up to date copy. All products are produced by independently owned and operated wood processing facilities. All other trademarks are trademarks of their respective owners. Registered England – 3037845 Document reference: 5.02.16



Photograph courtesy of Wilkinson-Eyre Architects & PLO Architects

